## **X**nightsbridge

## **DATASHEET**



## GDM150ISB

1G 2-way 10-150W (5-100W LED) intelligent dimmer - smoked bronze

www.mlaccessories.co.uk

DESCRIPTION  1G 2-way 10-150W (5-100W LED) intelligent dimmer - smoked bronze  0.036  FINISH  Smoked Bronze  Height - 56.3 Width - 25 Projection - 23 Recessed Depth - 22  MINIMUM MOUNTING BOX DEPTH  35mm  CONSTRUCTION  Construction - Premium grade steel Construction 2 - & ABS  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  SWITCH FUNCTION  1G 2-way 10-150W (5-100W LED) intelligent dimmer - smoked bronze  0.036  Construction  Construction  1 P20  Single Pole  SWITCH FUNCTION  2-Way
FINISHSmoked BronzeDIMENSIONS (MM)Height - 56.3 Width - 25 Projection - 23 Recessed Depth - 22MINIMUM MOUNTING BOX DEPTH35mmCONSTRUCTIONConstruction - Premium grade steel Construction 2 - & ABSIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleSWITCH FUNCTION2-Way
DIMENSIONS (MM)  Height - 56.3 Width - 25 Projection - 23 Recessed Depth - 22  MINIMUM MOUNTING BOX DEPTH  35mm  CONSTRUCTION  CONSTRUCTION  CONSTRUCTION  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  SWITCH FUNCTION  Premium grade steel Construction 2 - & ABS  IP20  Single Pole  Switch Function  2-Way
DIMENSIONS (MM)  Width - 25 Projection - 23 Recessed Depth - 22  MINIMUM MOUNTING BOX DEPTH  35mm  CONSTRUCTION  Construction - Premium grade steel Construction 2 - & ABS  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  SWITCH FUNCTION  2-Way
CONSTRUCTION  Construction - Premium grade steel Construction 2 - & ABS  IP RATING  IP20  INPUT VOLTAGE  SWITCH TYPE  Single Pole  SWITCH FUNCTION  Construction - Premium grade steel Construction 2 - & ABS  IP20  Single Pole  2-Way
CONSTRUCTION         Construction 2 - & ABS           IP RATING         IP20           INPUT VOLTAGE         230V 50Hz           SWITCH TYPE         Single Pole           SWITCH FUNCTION         2-Way
INPUT VOLTAGE 230V 50Hz SWITCH TYPE Single Pole 2-Way
SWITCH TYPE Single Pole SWITCH FUNCTION 2-Way
SWITCH FUNCTION 2-Way
·
40 450M (5 400M L 5D)
LOAD/MAX. LOAD 10-150W (5-100W LED)
TERMINAL CAPACITY 2 x 1.0mm² or 2 x 1.5mm²
ADDITIONAL FEATURES Intelligent dim
WARRANTY 2year(s)
MANUFACTURED IN ACCORDANCE WITH BS EN 60669-2
ORIGIN OF MANUFACTURE China
DECLARATION OF CONFORMITY (HELD ON FILE) Yes
<b>EAN</b> 5056270856132

Date Created: 24/05/2023 10:14





