

INSTALLATION & MAINTENANCE MANUAL  
**LWALL3**

---

Knightsbridge®  
the mark of quality



## GENERAL INSTRUCTIONS:

These instructions should be read carefully and retained after installation by the end user for future reference and maintenance.

These instructions should be used to aid installation of the following product;  
LWALL3

## SAFETY:

- Installation of this luminaire should only be carried out by a qualified electrician or competent person to the latest Building and current IEE Wiring Regulations (BS7671)
- Please isolate mains prior to installation/maintenance
- Check the total load on the circuit (including when this luminaire is fitted) does not exceed the rating of the circuit cable, fuse or circuit breaker
- Please note the IP (Ingress of Protection) rating of this luminaire when deciding the location for installation
- This product is Class I
- This product is non-dimmable
- This product is IP65 rated

## INSTALLATION:

- Provide power to the required point of installation. Suitable IP rated junctions boxes should be used where required
- Using the correct size Allen key remove the 3 grub screws securing the base plate of the luminaire (see Fig 1)




Fig 1

Remove all grub screws from base

- Using the base plate as a template mark the location of the fixing holes, and drill the holes ensuring not to infringe with any joists, gas or water pipes or electrical cables
- Feed mains cable through the rubber grommet to retain IP rating and secure base plate to the desired surface
- Carefully wire as shown in Fig 2




Fig 2

- Attach luminaire to the base plate with the Allen key grub screws
- Switch on and check for correct operation

## WARNING:

This product must be disconnected from the circuit if subjected to any high voltage or insulation resistance testing. Irreparable damage will occur if this instruction is not followed.

## GENERAL:

The LEDs fitted in this product are non-replaceable. The unit should be recycled in the correct manner when it reaches the end of its life. Check local authorities for where facilities exist. Clean with a soft dry cloth only, do not use aggressive cleaning products or solvents which may damage the product.

We recommend a light film of acid free oil to be applied 3-4 times a year. This will offer some protection from the elements when installed outside.

## WARRANTY:

This product has a warranty of 2 years from date of purchase. Failure to install this product in accordance with the current edition of the IEE Wiring Regulations, improper use, or removal of the batch codes will invalidate the warranty. If this product should fail within its warranty period it should be returned to the place of purchase for a free of charge replacement. ML Accessories does not accept responsibility for any installation costs associated with the replacement product. Your statutory rights are not affected. ML Accessories reserve the right to alter product specification without prior notice.