

230V LED Linkable Strip light



MLA part code	UCLED4W3K	UCLED9W3K	UCLED13W3K	UCLED18W3K	UCLED22W3K
Description	Linear Ultra-Thin switchable LED Strip light				
ErP Class	A+	A	A	A	A
Weight (kg)	0.095	0.155	0.223	0.288	0.35
Wattage (W)	4	9	13	18	22
Lumens (lm)	317	645	954	1456	1555
Efficacy (lm/W)	71	76	76	81	78
P.F	0.52	0.52	0.54	0.52	0.54
Beam Angle (°)	140				
Overall dimensions (mm)	277(l) 28(w) 36(p)	538(l) 28(w) 36(p)	838(l) 28(w) 36(p)	1138(l) 28(w) 36(p)	1438(l) 25(w) 36(p)
CCT	3000K				
LED Colours	Warm White				
CRI	>80				
LED type	SMD				
Running current (A)	0.036	0.073	0.11	0.15	0.18
Input voltage	Mains 230V 50Hz				
Construction	Polycarbonate				
Class	Class II				
IP rating	IP20				
Warranty	3 Year				
Supplied with	2m of cable with connector and 2 mounting clips		2m of cable with connector and 3 mounting clips		
Additional Accessories available	Link cable 250mm (UC250) Link cable 500mm (UC500) Link cable 1000mm (UC1000)				
Photometric data	No				
Dimmable	No				
Instruction sheet	Yes				
Origin of Manufacture	China				
Quality assurance system	ISO9001				
Declaration of Conformity (held on file)	Yes				
Manufactured & accordance with	EN60598				

