Knightsbridge

DATASHEET



SFR9901BNW

Screwless 13A 1G switched socket with dual USB charger (2.1A) - black nickel with white insert

www.mlaccessories.co.uk

DESCRIPTIONScrewless 13A 1G switched socket with dual USB char black nickel with white insertFINISHBlack NickelINSERT COLOURWhiteDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASS1IP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGINGSV DC 2.1A (shared)ADDITIONAL FEATURESOverload and short circuit protection	ger (2.1A) -
INSERT COLOURUnitedINSERT COLOURWhiteDIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIIP RATINGISWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
DIMENSIONS (MM)Height - 87.5 Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
DIMENSIONS (MM)Width - 87.5 Projection - 4.3MINIMUM MOUNTING BOX DEPTH25-35mm (dependent on wiring conditions)CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
CONSTRUCTIONConstruction - Premium grade steelCLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
CLASSIIP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
IP RATINGIP20INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
INPUT VOLTAGE230V 50HzSWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
SWITCH TYPESingle PoleEARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
EARTH TERMINALYesLOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
LOAD/MAX. LOAD13ATERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
TERMINAL CAPACITY2 x 2.5mm² or 1 x 4.0mm²NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
NO. OF USB PORTS2NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
NO. OF TYPE-A PORTS2USB CHARGING5V DC 2.1A (shared)	
USB CHARGING 5V DC 2.1A (shared)	
ADDITIONAL FEATURES	
ADDITIONAL PEATORES Overload and short circuit protection	
WARRANTY 2year(s)	
MANUFACTURED IN ACCORDANCE WITH BS-1363-2, BS EN 60950-1	
ORIGIN OF MANUFACTURE China	
DECLARATION OF CONFORMITY (HELD ON FILE) Yes	
EAN 5055832946205	

Date Created: 26/07/2022 16:37



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

