

230V LED CCT Batten Standard



MLA part code	BATC4	BATC5	BATC6
Description	230V 4ft LED CCT Batten	230V 5ft LED CCT Batten	230V 6ft LED CCT Batten
Finish	White		
Nett weight (kg)	1.25	1.65	1.9
Dimensions (mm)	Length – 1170 Height – 71 Width - 61	Length – 1470 Height – 71 Width - 61	Length – 1734 Height – 71 Width - 61
Circuit Wattage (W)	22	35	40
Lumens (lm)	3000K – 2545 ± 5% 4000K – 2765 ± 5% 6000K – 2745 ± 5%	3000K – 3775 ± 5% 4000K – 4160 ± 5% 6000K – 4160 ± 5%	3000K – 4645 ± 5% 4000K – 5045 ± 5% 6000K – 4955 ± 5%
Efficacy (lm/W)	3000K - 112 4000K – 129 6000K – 120	3000K - 106 4000K – 126 6000K – 117	3000K - 116 4000K – 129 6000K – 123
CCT	3000K - Warm white 4000K - Cool white 6000K - Daylight		
CRI	>80		
Running current (A)	0.1	0.15	0.18
Inrush current	40A		
Power factor	0.96	0.97	0.97
Beam angle	137°		
Life span (Hrs)	50,000		
Input voltage	Mains 230V 50Hz		
Construction	Steel & Polycarbonate		
Class	Class I		
IP rating	IP20		
Dimmable	No		
Warranty	5 Years		
Origin of Manufacture	China		
Declaration of Conformity (held on file)	Yes		
Manufactured in accordance with	BS EN 60598		
EAN	5055832993995	5055832994039	5055832994077

