
PRCLEDEM / PRCLEDEM4



ISSUE: AKAPR18VOL2

LED surface mount - Emergency





MLA part code	PRCLEDEM	PRCLEDEM4
Description	LED surface mount-emergency	
Finishes	White with frosted diffuser	
Nett weight (kg)	3.39	3.2
Construction	Steel and polycarbonate	
Class	Class I	
Overall dimensions (mm)	Length – 1490	Length – 1229
	Width – 198	Width – 198
	Projection - 68	Projection - 68
Wattage (W)	49	43
Lumens (lm)	6000 <u>+</u> 5%	4700 <u>+</u> 5%
Lumens (Im) in emergency mode	600 <u>+</u> 5%	730 <u>+</u> 5%
Efficacy (lm/W)	127	109
Input voltage	Mains 230V 50Hz	
P.F	0.9	
Operating current (A)	0.215	0.222
CCT	4000K	
LED Colour	Cool white	
CRI	>80	
IP rating	IP20	
Life span (Hrs)	35,000	
Battery	Nickel Cadmium 1500mAh 12V (10 cell)	
Warranty	5 years (excluding battery)	
Origin of Manufacture	China	
Declaration of Conformity (held on file)	Yes	
Manufactured & accordance with	EN60598-2-1	
EAN	5055832973935	5055832986515
		ℤ (€

