



DATASHEET



FL16AW

230V IP55 Twin Spot LED Security Light - White

www.mlaccessories.co.uk



| | |
|-----------------------|---|
| MLA PART CODE | FL16AW |
| DESCRIPTION | 230V IP55 Twin Spot LED Security Light - White |
| NET WEIGHT (KG) | 0.46 |
| FINISH | White |
| DIFFUSER | Prismatic |
| DIMENSIONS (MM) | Width - 141 Projection - 113 Overall Height - 176 |
| CONSTRUCTION | Construction - Polycarbonate Construction 2 - & die-cast aluminium |
| CLASS | II |
| IP RATING | IP55 |
| WATTAGE (W) | 16 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1300 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 85.03 |
| CIRCUIT WATTAGE (W) | 15.475 |
| CCT | 5000K |
| LIGHT COLOUR | White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.123 |
| DISPLACEMENT FACTOR | >0.5 |
| SVM | 0.006 |
| PST-LM | 0.092 |
| BEAM ANGLE (DEGREES) | 85 |
| L70B50 LIFESPAN (HRS) | 60,000 |
| DIMMABLE | No |

| | |
|---|-------------------------|
| OPERATING TEMPERATURE | 40°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | Blind grommet |
| SENSOR TYPE | PIR |
| SENSOR OVERRIDE | No |
| SENSOR DETECTION ANGLE (DEGREES) | 180 |
| OPTIMUM DETECTION RANGE (M) | 10 |
| SENSOR DURATION | 10 seconds - 15 minutes |
| SENSOR LUX SETTINGS | 5 lux - 1000 lux |
| STANDBY POWER | <0.5W |
| WARRANTY | 3year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270886689 |

Date Created: 07/11/2022 12:55

