



## DATASHEET



### BATS4

230V 4ft 22W LED Batten- 4000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



|                               |  |
|-------------------------------|--|
| MLA PART CODE                 | <b>BATS4</b>   |
| DESCRIPTION                   | 230V 4ft 22W LED Batten- 4000K                                   |
| NET WEIGHT (KG)               | 1.28   |
| FINISH                        | White  |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Length - 1225<br>Width - 61<br>Projection - 71                   |
| CONSTRUCTION                  | Construction - Pressed steel<br>Construction 2 - & polycarbonate |
| CLASS                         | I  |
| IP RATING                     | IP20   |
| WATTAGE (W)                   | 22   |
| LAMP TECHNOLOGY               | LED  |
| LAMP INCLUDED                 | Yes  |
| LUMENS (LM)                   | 2625   |
| LUMENS LIGHT SOURCE ONLY (LM) | 3370   |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LMMW)               | 147.56   |
| CIRCUIT WATTAGE (W)           | 22.85  |
| CCT                           | 4000K  |
| LIGHT COLOUR                  | Cool White   |
| CRI                           | >80  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.103  |
| DISPLACEMENT FACTOR           | >0.9   |
| SVM                           | 0.841  |



# Knightsbridge

|  |  |
|--|--|
| PST-LM                                   | 0.038  |
| BEAM ANGLE (DEGREES)                     | 115  |
| LIFE SPAN (HRS)                          | 50,000   |
| L70B50 LIFESPAN (HRS)                    | 50,000   |
| DIMMABLE                                 | No   |
| OPERATING TEMPERATURE                    | -20~50°C   |
| INPUT VOLTAGE                            | 230V 50Hz  |
| CABLE GLAND INCLUDED                     | No   |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 20W<br>OUTPUT VOLTAGE - 30-43V<br>OUTPUT CURRENT - 480mA<br>POWER FACTOR - 0.95<br>EFFICIENCY FULL LOAD - 88.56<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta) - -20~50°C<br>CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY                                 | 5year(s)   |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598  |
| ORIGIN OF MANUFACTURE                    | China  |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes  |
| EAN                                      | 5055832993155  |

Date Created: 09/03/2022 13:10

