
## **Knightsbridge**

## DATASHEET

## **BATS5EMH**

230V 5ft 55W LED Emergency High Lumen Batten-4000K

www.mlaccessories.co.uk



| MLA PART CODE                 | BATS5EMH   |
|-------------------------------|--|
| DESCRIPTION                   | 230V 5ft 55W LED Emergency High Lumen Batten- 4000K              |
| NET WEIGHT (KG)               | 1.83   |
| FINISH                        | White  |
| DIFFUSER                      | Opal   |
| DIMENSIONS (MM)               | Length - 1525<br>Width - 61<br>Projection - 71                   |
| CONSTRUCTION                  | Construction - Pressed steel<br>Construction 2 - & polycarbonate |
| CLASS                         | I  |
| IP RATING                     | IP20   |
| WATTAGE (W)                   | 55   |
| LAMP TECHNOLOGY               | LED  |
| LAMP INCLUDED                 | Yes  |
| LUMENS (LM)                   | 5925   |
| LUMENS LIGHT SOURCE ONLY (LM) | 8210   |
| LUMEN TOLERANCE               | 5%   |
| EFFICACY (LM/W)               | 147.49   |
| LUMENS EMERGENCY MODE (LM)    | 230  |
| CIRCUIT WATTAGE (W)           | 55.68  |
| ССТ                           | 4000K  |
| LIGHT COLOUR                  | Cool White   |
| CRI                           | >80  |
| SDCM                          | <6   |
| RUNNING CURRENT (A)           | 0.252  |
| DISPLACEMENT FACTOR           | >0.9   |



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification. ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.



## **Knightsbridge**

| SVM                                      | 0.873   |
|--|---|
| PST-LM                                   | 0.035   |
| BEAM ANGLE (DEGREES)                     | 135   |
| LIFE SPAN (HRS)                          | 50,000  |
| L70B50 LIFESPAN (HRS)                    | 50,000  |
| DIMMABLE                                 | No  |
| EMERGENCY                                | Maintained / Non-maintained / Switched  |
| OPERATING TEMPERATURE                    | -20~50°C  |
| INPUT VOLTAGE                            | 230V 50Hz   |
| CABLE GLAND INCLUDED                     | No  |
| DRIVER                                   | DRIVER TYPE - Constant Current<br>MAX. OUTPUT - 50W<br>OUTPUT VOLTAGE - 29-43V<br>OUTPUT CURRENT - 1200mA<br>POWER FACTOR - 0.95<br>EFFICIENCY FULL LOAD - 91.33<br>ISOLATION - SELV<br>AMBIENT TEMPERATURE (Ta)20~50°C<br>CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY                                 | 5year(s)  |
| WARRANTY INFORMATION                     | (excluding battery)   |
| MANUFACTURED IN ACCORDANCE WITH          | BS EN 60598   |
| ORIGIN OF MANUFACTURE                    | China   |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes   |
| EAN                                      | 5056270807233   |
| Data Croated: 00/02/2022 12:10           |   |

Date Created: 09/03/2022 13:10

Ж



