



DATASHEET



BATS5

230V 5ft 37W LED Batten- 4000K

www.mlaccessories.co.uk



| | |
|-------------------------------|--|
| MLA PART CODE | BATS5 |
| DESCRIPTION | 230V 5ft 37W LED Batten- 4000K |
| NET WEIGHT (KG) | 1.59 |
| FINISH | White |
| DIFFUSER | Opal |
| DIMENSIONS (MM) | Length - 1525 Width - 61 Projection - 71 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | I |
| IP RATING | IP20 |
| WATTAGE (W) | 37 |
| LAMP TECHNOLOGY | LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 4290 |
| LUMENS LIGHT SOURCE ONLY (LM) | 5425 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 148.41 |
| CIRCUIT WATTAGE (W) | 36.56 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.167 |
| DISPLACEMENT FACTOR | >0.9 |
| SVM | 0.751 |



Knightsbridge

| | |
|--|--|
| PST-LM | 0.036 |
| BEAM ANGLE (DEGREES) | 145 |
| LIFE SPAN (HRS) | 50,000 |
| L70B50 LIFESPAN (HRS) | 50,000 |
| DIMMABLE | No |
| OPERATING TEMPERATURE | -20~50°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE GLAND INCLUDED | No |
| DRIVER | DRIVER TYPE - Constant Current MAX. OUTPUT - 36W OUTPUT VOLTAGE - 29-43V OUTPUT CURRENT - 840mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 87.02 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C |
| WARRANTY | 5year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5055832993193 |

Date Created: 09/03/2022 13:10

