


DATASHEET



BATSCWEM5

230V 5ft 22/41W CCT Adjustable Emergency Batten

www.mlaccessories.co.uk



MLA PART CODE	BATSCWEM5
DESCRIPTION	230V 5ft 22/41W CCT Adjustable Emergency Batten
NET WEIGHT (KG)	1.83
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1525 Width - 61 Projection - 71
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	22/41
LAMP TECHNOLOGY	LED
LUMENS (LM)	2970/3300/3210, 5170/6040/5630
LUMENS LIGHT SOURCE ONLY (LM)	6520
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	160.58
LUMENS EMERGENCY MODE (LM)	360
CIRCUIT WATTAGE (W)	40.64
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.18
DISPLACEMENT FACTOR	>0.9
SVM	0
PST-LM	0
BEAM ANGLE (DEGREES)	145
L70B50 LIFESPAN (HRS)	60,000

DIMMABLE	No
EMERGENCY	Maintained / Non-maintained / Switched
SELF-TEST	No
OPERATING TEMPERATURE	-5~50°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 21/42W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 480/960mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 96.9 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -20~50°C CASE TEMPERATURE (Tc) - 75°C
BATTERY INCLUDED	Yes
WARRANTY	5year(s)
WARRANTY INFORMATION	(excluding battery)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270881578

Date Created: 30/08/2023 10:43

