


DATASHEET



CPLCW18

230V IP54 Tri-Wattage and CCT Dual Mount Downlight - 12/15/18W

www.mlaccessories.co.uk



MLA PART CODE	CPLCW18
DESCRIPTION	230V IP54 Tri-Wattage and CCT Dual Mount Downlight - 12/15/18W
NET WEIGHT (KG)	0.385
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 216 Height - 17.6 Projection - 17.6 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 65-190
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP54
WATTAGE (W)	12 / 15 / 18
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1115/1235/1140/1390/1560/1420/1675/1875/1695
LUMENS LIGHT SOURCE ONLY (LM)	2330
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	126
CIRCUIT WATTAGE (W)	18.5
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.083
DISPLACEMENT FACTOR	>0.9
SVM	0.119
PST-LM	0.04

Knightsbridge

BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	Yes*
IC RATED	No
OPERATING TEMPERATURE	-20 ~ 35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270886146

Date Created: 06/10/2025 13:11

