

DATASHEET



CPLCW24

230V IP54 Tri-Wattage and CCT Dual Mount Downlight - 18/21/24W

www.mlaccessories.co.uk



MLA PART CODE	CPLCW24
DESCRIPTION	230V IP54 Tri-Wattage and CCT Dual Mount Downlight - 18/21/24W
NET WEIGHT (KG)	0.638
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Diameter - 292 Height - 17.6 Projection - 17.6 Minimum Void - 50
CUT-OUT (MM)	Cut-out Diameter - 115-255
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP54
WATTAGE (W)	18 / 21 / 24
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1885/2080/1930/2160/2415/2210/2400/2710/2455
LUMENS LIGHT SOURCE ONLY (LM)	3215
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	131
CIRCUIT WATTAGE (W)	24.4
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.111
DISPLACEMENT FACTOR	>0.9
SVM	0.128
PST-LM	0.034

Knightsbridge

BEAM ANGLE (DEGREES)	115
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	Yes*
IC RATED	No
OPERATING TEMPERATURE	-20 ~ 35°C
INPUT VOLTAGE	230V 50Hz
CABLE LENGTH (M)	0.3
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270886207

Date Created: 06/10/2025 13:11

