

## DATASHEET



### T8BLED14

230V 20W LED Batten 1225mm (4ft) 4000K

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	T8BLED14
DESCRIPTION	230V 20W LED Batten 1225mm (4ft) 4000K
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1225 Width - 60 Projection - 85
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
WATTAGE (W)	20
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2300
LUMENS LIGHT SOURCE ONLY (LM)	2955
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	115
CIRCUIT WATTAGE (W)	21.29
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.185
DISPLACEMENT FACTOR	>0.9
SVM	0.888
PST-LM	0.037



# Knightsbridge

BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	30,000
L70B50 LIFESPAN (HRS)	50,000
DIMMABLE	No
OPERATING TEMPERATURE	-15~45°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 20W OUTPUT VOLTAGE - 35-44V OUTPUT CURRENT - 480mA POWER FACTOR - 0.5 EFFICIENCY FULL LOAD - 88.00 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - -15~45°C CASE TEMPERATURE (Tc) - 70°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832934547

Date Created: 09/03/2022 13:13

