



DATASHEET



PRECW4

Preceptor 230V 4ft 30W Modular CCT and Wattage Adjustable UGR19 Linear Fitting

www.mlaccessories.co.uk



MLA PART CODE	PRECW4
DESCRIPTION	Preceptor 230V 4ft 30W Modular CCT and Wattage Adjustable UGR19 Linear Fitting
FINISH	White
DIFFUSER	Prismatic
DIMENSIONS (MM)	Length - 1180 Width - 206 Projection - 80
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	18/21/26/30
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2200/2400/2300,2600/2800/2700,3200/3400/3300,3600/3900/3700
LUMENS LIGHT SOURCE ONLY (LM)	3000/3200/3100,3500/3700/3600,4300/4600/4400,4900/5200/5000
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	172/169/170/166
CIRCUIT WATTAGE (W)	19/23/27/32
CCT	3000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.09/0.10/0.12/0.14
DISPLACEMENT FACTOR	>0.7
SVM	0.01
PST-LM	0.1
BEAM ANGLE (DEGREES)	70
L70B50 LIFESPAN (HRS)	100000

LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 50-133V OUTPUT CURRENT - 0.200/0.250/0.300/0.350mA POWER FACTOR - 0.95 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	7year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061276518

Date Created: 27/11/2025 17:22