



## DATASHEET



### PRECW5

#### Preceptor 230V 5ft 45W Modular CCT and Wattage Adjustable UGR19 Linear Fitting

[www.mlaccessories.co.uk](http://www.mlaccessories.co.uk)



MLA PART CODE	PRECW5
DESCRIPTION	Preceptor 230V 5ft 45W Modular CCT and Wattage Adjustable UGR19 Linear Fitting
FINISH	White
DIFFUSER	Prismatic
DIMENSIONS (MM)	Length - 1480 Width - 206 Projection - 80
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	24/30/36/44
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2900/3200/3000,3600/3900/3700,4200/4500/4400,5100/5400/5200
LUMENS LIGHT SOURCE ONLY (LM)	3900/4200/4000,4800/5200/4900,5800/6200/5900,7000/7500/7200
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	169/167/167/170
CIRCUIT WATTAGE (W)	25/32/38/45
CCT	3000K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.11/0.14/0.16/0.19
DISPLACEMENT FACTOR	>0.7
SVM	0.01
PST-LM	0.1
BEAM ANGLE (DEGREES)	70
L70B50 LIFESPAN (HRS)	100000

LED COMPATIBLE	Yes
DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT
OPERATING TEMPERATURE	-20~50°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 60W OUTPUT VOLTAGE - 84-200V OUTPUT CURRENT - 0.200/0.250/0.300/0.350mA POWER FACTOR - 0.95 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	7year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061276563

Date Created: 27/11/2025 17:23