


DATASHEET



LEDT5WCW

24V 5W LED Linkable Triangular Striplight 6000K (500mm)

www.mlaccessories.co.uk



MLA PART CODE	LEDT5WCW
DESCRIPTION	24V 5W LED Linkable Triangular Striplight 6000K (500mm)
NET WEIGHT (KG)	0.214
DIMENSIONS (MM)	Length - 500 Width - 33 Projection - 20
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	III
IP RATING	IP20
WATTAGE (W)	5
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	580
LUMENS LIGHT SOURCE ONLY (LM)	745
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	146.2
CIRCUIT WATTAGE (W)	5.1
CCT	6000K
LIGHT COLOUR	Daylight
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.209
BEAM ANGLE (DEGREES)	90
L70B50 LIFESPAN (HRS)	35,000
DIMMABLE	Driver dependent
OPERATING TEMPERATURE	-20~40°C



Knightsbridge

INPUT VOLTAGE	24V DC
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055559132080

Date Created: 09/03/2022 13:18

