



DATASHEET



MLR6045SD

230V IP44 600 x 450mm Back-lit LED Bathroom Mirror with Demister, Shaver Socket and Motion Sensor

www.mlaccessories.co.uk



| | |
|-------------------------------|--|
| MLA PART CODE | MLR6045SD |
| DESCRIPTION | 230V IP44 600 x 450mm Back-lit LED Bathroom Mirror with Demister, Shaver Socket and Motion Sensor |
| NET WEIGHT (KG) | 5.85 |
| DIMENSIONS (MM) | Height - 600 Width - 450 Projection - 65 Base Width - 355 Base Height - 500 Base Depth - 60 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & glass |
| CLASS | I |
| IP RATING | IP44 |
| WATTAGE (W) | 19 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 1060 |
| LUMENS LIGHT SOURCE ONLY (LM) | 2070 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 101.62 |
| CIRCUIT WATTAGE (W) | 20.38 |
| CCT | 4000K |
| LIGHT COLOUR | Cool White |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.102 |
| DISPLACEMENT FACTOR | >0.7 |



Knightsbridge

| | |
|--|---|
| SVM | 0.003 |
| PST-LM | 0.001 |
| BEAM ANGLE (DEGREES) | 270 |
| LIFE SPAN (HRS) | 20,000 |
| L70B50 LIFESPAN (HRS) | 30,000 |
| LED COMPATIBLE | Yes |
| DIMMABLE | No |
| OPERATING TEMPERATURE | 40°C |
| INPUT VOLTAGE | 230V 50Hz |
| SECONDARY VOLTAGE | 115/230V |
| LOAD/MAX. LOAD | 20VA |
| DRIVER | DRIVER TYPE - Constant Voltage MAX. OUTPUT - 20W OUTPUT VOLTAGE - 24V OUTPUT CURRENT - max 830mA POWER FACTOR - 0.8 EFFICIENCY FULL LOAD - 80 ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C |
| SENSOR TYPE | PIR |
| SENSOR OVERRIDE | No |
| OPTIMUM DETECTION RANGE (M) | 0.030 |
| STANDBY POWER | 0.5W |
| WARRANTY | 1year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270821673 |

Date Created: 09/03/2022 13:21

