

PTFE Tapes

For Gas and Water



Material:

Features:

- Material: PTFE (poly-tetra-fluoro-ethylene) - Teflon tape.
- Yellow - suitable for use with gas and hot water pipes.
- White - suitable for use with water only.
- Resistant to almost all chemicals.
- Prevents fluid and pressure loss.



Technical Data - PTFE-TAPE/G

Property	Value
Total Thickness	0.2mm (±0.02)
Elongation	40% min.
Tensile Strength	10 Mpa
PH Range	1 - 14
Lubricant Content	0.1%
Temperature Rating	-190°C to +370°C

Technical Data - PTFE-TAPE/W

Property	Value
Total Thickness	0.08mm (±0.002)
Elongation	40% min.
Tensile Strength	10 Mpa
PH Range	1 - 14
Lubricant Content	0.1%
Temperature Rating	-190°C to +370°C

Item No.	Colour	W (mm)	L (m)	Thickness (mm)
PTFE-TAPE/G	Yellow	12	5	0.2
PTFE-TAPE/W	White	12	12	0.08

The above information is given only as a guide, the user should ensure that the performance of the product is sufficient for application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. KrimpTerm cannot be held responsible for product failure unless full testing has been carried out. The user has to decide on the tapes suitability for their own applications.