













	1
BOXER 300 TECHNICAL DATA	
Energy source	3 x LR03 (3 x AAA), 3 alkaline batteries supplied (4,5 V)
Light source	3 x 5mm LEDs, long life (do not need replacing)
Lighting surface area	40 m2 (new batteries)
Temperature of use	-25°Cto +50°C
Materials	Case : Polyamide PA + mineral
	Front shock resistance : Polyurethane PU
	Glass : Polycarbonate
Headband	66 % Polyester, 29 % elastodiene, 5 % polyamide
	Removable, washable, hypoallergenic, adjustable
	Maximum head circumference 980 mm (mini 350 mm)
Weight with batteries	90 grams
Operating duration	Up to 150 hours (see diagram A)
Multi-purpose use	Frontal (with headband)
	Free-standing (with or without headband)
	Clipped to a helmet with a 20x3mm slot (without headband)
	Clipped to a belt or pocket
Safety	Switch-on safety device
	Electronic protection of LEDs (if polarity inverted)
	Self-cleaning contacts
Water-tightness	IP 54, weather-resistant (rain, snow)
Accessories	Kit of 4 hooks for helmet without slot (optional)
Guarantee	3 years (see general sales conditions)
40 m ² Diagram A	



17 route de Nanfray 74960 CRAN-GEVRIER

Tél: (33) (0) 4 50 69 39 15