



SKT SURF ANG 16A 5P 415V 6H IP67

WALL-MOUNTING SOCKET-OUTLET 90°3P+N+E 16A 380V 6H IP67



509146

TOPTER WALL MOUNTED SOCKET, 90° ANGLED, 16A 3P+N+E 380-415V 50-60HZ 6H IP67

TECHNICAL DATA		REGISTRY	
Rated current	16A	Net weight	0.38KG
Rated operating voltage	400V	Min order quantity	1
Poles	3P+N+ $\frac{1}{2}$	EAN Code	8014950040254
Clock Position	6h	Gross Weight	0.45KG
Frequency	50/60Hz	REFERENCE STANDARDS	STANDARDS
IP Protection degree	IP67	EN IEC 63000:2018	2014/35/EU (LVD)
Colour	Grey RAL 7042	EN 60309-1:1999/A1AC:2014	2012/19/EU (WEEE)
Min conductor section	1mm ²	EN 60309-1:1999/A2:2012	2011/65/EU (RoHS)
Shock resistance	IK08 according to IEC/EN 62262	EN 60309-2:1999	
Rated insulation voltage	690 V	EN 60309-1:1999	
Manufacturing material	Technopolymer Recyclable Palazzoli	EN 60309-2:1999/A2:2012	
Execution	Wall mounting	EN 60309-1:1999/A1:2007	
Flange dimensions	-	EN 60309-2:1999/A1:2007	
Standard plug-socket	IEC 60309-2		