SKT SURF ANG 63AMP 5P 415V IP67

WALL-MOUNTING SOCKET-OUTLET 90°

509346

TOPTER WALL MOUNTED SOCKET, 90° ANGLED, 63A 3P+N+E 380-415V 50-60HZ 6H IP67

TECHNICAL DATA

Rated current	63A
Rated operating voltage	400V
Poles	3P+N+⏚
Clock Position	6h
Frequency	50/60Hz
IP Protection degree	IP67
Colour	Grey RAL 7042
Min conductor section	4mm^2
Shock resistance	IK08 according to IEC/EN 62262
Rated insulation voltage	690 V
Manufacturing material	Technopolymer Recyclable Palazzoli
Execution	Wall mounting
Flange dimensions	-
Standard plug-socket	IEC 60309-2

REGISTRY

Net weight	1.10KG
Min order quantity	1
EAN Code	8014950040322
Gross Weight	1.28KG

REFERENCE STANDARDS

EN IEC 63000:2018
EN 60309-1:1999/A1AC:2014
EN 60309-1:1999/A2:2012
EN 60309-2:1999
EN 60309-1:1999
EN 60309-2:1999/A2:2012
EN 60309-1:1999/A1:2007
EN 60309-2:1999/A1:2007

STANDARDS

2014/35/EU (LVD)
2012/19/EU (WEEE)
2011/65/EU (RoHS)