SKT SW INT 16A 5P 415V IP67 6H MOULDED

SURFACE SWITCH INTERLOCK 3P+N+E 16A 400V 6H IP66/IP67

PM16/3408NFPB

TOPTER switched interlocked socket 3P+N+T 16A 380-415V 50-60Hz 6h IP66/IP67

TECHNICAL DATA	
Rated current	16A
Frequency	50/60Hz
Poles	3P+N+⏚
Dimensions	260X108X135mm (HWD)
Clock Position	6h
Storage room temperature MAX	+70°C
IP Protection degree	IP66/IP67
Rated operating voltage	400V
Manufacturing material	Technopolymer Recyclable Palazzoli

REGISTRY	
Net weight	0.70KG
Gross Weight	1.00KG
EAN Code	8014950038190
Min order quantity	1
Dimensions	260X108X135mm (HWD)

REFERENCE STANDARDS	STANDARDS
EN 60309-1:1999/A1AC:2014	2014/35/EU (LVD)
EN 60309-1:1999/A2:2012	2012/19/EU (WEEE)
EN 60309-2:1999	2011/65/EU (RoHS)
EN 60309-1:1999	
EN 60309-2:1999/A2:2012	
EN 60309-1:1999/A1:2007	
EN 60309-4:2007/A1:2012	
EN 60309-2:1999/A1:2007	
EN 60309-4:2007	
EN IEC 63000:2018	