



Amenity lights offering reliability, style and performance for open areas



5 Year Warranty



IK08



✓ IES Files



Double Insulated

Eterna[®]
Everyday Lighting For Professionals

LED AMENITY CEILING / WALL LIGHTS

Long life, energy efficient utility fitting perfect for domestic or commercial settings including perimeter lighting, paths, gardens and porches, communal areas, staircases and many more.

- Polycarbonate / ABS construction • Stainless steel screws
- Multiple low power LED array & optically optimised diffuser: ensures a soft, even lighting effect with no degradation of light output

LED LAMP SPECIFICATIONS:	SHFULL	SHEYE
Luminaire lumens (with diffuser)	1150 lm	790 lm
Lumens from chip (no diffuser)	1280 lm	1120 lm
Useful lumens	1120 lm	750 lm
Rated Wattage	11W	11W
Rated luminous flux	1120 lm	750 lm
Nominal life time of the lamp	50,000 hrs	50,000 hrs
Colour temperature	4000K	4000K
Number of switching cycles before premature lamp failure	≥15,000	≥15,000
Warm-up time up to 60% of the full light output	Instant full light	Instant full light
Dimmable	No	No
Nominal beam angle	120°	120°
Rated power	11W	11W
Rated lamp lifetime	50,000 hrs	50,000 hrs
Displacement factor	≥0.8	≥0.8
Lumen maintenance factor at end of nominal life	≥0.8	≥0.8
Starting time	Instant full light	Instant full light
Colour rendering	≥80	≥80
Colour consistency	Within a six step Macadam ellipse	Within a six step Macadam ellipse
Rated peak intensity	324cd	257cd
Rated beam angle	120°	120°
Voltage / Frequency	240V~50Hz	240V~50Hz
Lumen efficacy	104 lm / W	71 lm / W
This product contains a Light Source of Energy Efficiency Class	E	F
Class 2 double insulated		
Not suitable for accent lighting		

MICROWAVE VERSIONS:

- SENSORMW included
- Rated Load - 800W (resistive), 400W (inductive), 270W (LED)
- Adjustable detection angle: up to 150°
- Power consumption: <0.5W
- Adjustable detection range: Max. 6m
- Adjustable time setting: 5 seconds - 30 minutes
- Adjustable Lux control: 2-50 lux
- Push connect terminals: for ease of connection

Code	Version	Diffuser	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP / IK Rating	MOM / OPQ
SHFULLBK	Standard	Full	Black	11W	4000K	1150 lm	50,000 hrs	IP66 IK08	1 / 10
SHFULLWH			White						
SHEYEBK		Eyelid	Black						
SHEYEWH			White						
SHFULLMWBK	Microwave	Full	Black	11W	4000K	1150 lm	50,000 hrs	IP66 IK08	1 / 10
SHFULLMWWH			White			790 lm			
SHEYEMWBK		Eyelid	Black						

