

EMERGENCY LED BATTEN



MLA part code	T8BLED15EM	T8BLED16EM	T8BLED25EM	T8BLED26EM
Description	Twin LED Batten Emergency			
ErP Class	A++	A+	A+	A+
Weight (kg)	1.66	1.89	2.49	1.89
Wattage (W)	26	30	50	60
Lumens (lm)	3000	3450	5250	6500
EM Lumens (lm)	670	680	660	660
Efficacy (lm/W)	115	115	105	108
Emergency duration	3 Hours			
Beam Angle (°)	150			
Overall dimensions (mm)	1525(l) 60(w)85(p)	1790(l)60(w)85(p)	1525(l) 95(w)85(p)	1790(l)95(w)85(p)
CCT	4000K			
LED Colours	Cool White			
Running Current (A)	0.126	0.147	0.245	0.266
PF	>0.9			
Input voltage	Mains 230V 50Hz			
Lifespan (hrs)	30,000			
Construction	Metal			
Class	1			
IP rating	IP20			
Warranty	5 Years			
Photometric data	Yes			
Dimmable	No			
Instruction sheet	Yes			
Origin of Manufacture	China			
Quality assurance system	ISO9001			
Declaration of Conformity (held on file)	Yes			
Manufactured & accordance with	BS EN 60598			

