Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC						
Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE						
Model identifier: 5260201012M						
Type of light source:						
Lighting technology used:	LFD	Non-directional or	NDLS			

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Source (CLS): Colour-tuneable light source: No Envelope: No Anti-glare shield: No Dimmable: No Product parameters Parameter Value Parameter Value General product parameters: Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer Liseful luminous flux (dusa) Source (CLS): Envelope: Source (CLS): Source (CLS): Correlated colour (2000) Correlated c

mode (kWh/10 up to the neare	00 h), rounded st integer		class	
Useful luminou indicating if it r in a sphere (3)	us flux (φuse), efers to the flux 60º), in a wide n a narrow cone	950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pexpressed in W	oower (P _{on}),	8,6	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	15	Spectral power	See image
dimensions	Width	40	distribution in the	in last page
without	Depth	55		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	69	
		Chromaticity	0,440	
		coordinates (x and y)	0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	8	Survival factor	1,00	
the lumen maintenance factor	0,96			
Parameters for LED and OLED mains light sources:				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0	

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

