

## KS616

Up to 6 Exchange Lines  
 Configured for up to 16 Extensions 201 – 216  
 Expandable up to 32 Extensions via slot in cards  
 Key Phone Compatible (KP616)  
 Auto Attendant (DISA) with 30 seconds OGM  
 80 System Speed dials  
 Auto Fax Transfer in Auto-attendant  
 Transfer & Pickup  
 Caller ID compatible  
 Remote Programming  
 Operator Call  
 Hot Line  
 Broadcasting /Tannoy  
 Call Forward to Secretary and on Busy  
 External Music On-Hold Port  
 Conference Call  
 Programmable Call Restrictions & Call Barring  
 Exchange Lines 'in use' LED's  
 CE & RoHS Compliant



## Specifications

Capacity	CO Lines: 6      Extensions: 16
Exterior Jack	Standard RJ11 Sockets: Line Port, Extension Port & COM Port. 3.5mm Audio Socket: External Music Input Port
Communication	8 Channels
Transmission	Extension to Extension $\leq 1.5\text{dB}$ Extension to Trunk Line $\leq 2.0\text{dB}$
Ring Current	AC65v / 50Hz
Feedback current	DC33V/25mA
Degree of Unbalance about Earth	300Hz---600Hz $\leq 40\text{dB}$ 600Hz---3400Hz $\leq 46\text{dB}$
Dial Mode	DTMF
Signal Tone	Internal dial tone: 450Hz, Continuous sine wave Internal ring-back tone: 450Hz, sine wave, 1s on / 4s off Internal busy tone: 450 Hz, sine wave, 0.3s on / 0.3s off Internal confirmation tone: 450 Hz, sine wave, 1s on Internal error tone; 450 Hz, sine wave, 0.3s on / 0.3s off
Caller ID	Receive: DTMF, FSK (Bell 202) Send: FSK (Bell 202)
Power Supply	AC230V +/- 10%, 12w
Line & Extension Socket Connection	Pins 3 and 4 of RJ11 Socket
Dimensions	44 x 13 x 36 cm - weight 4kg