

Product Code: CHOICE PR2n

Description: Two channel programmer, designed for separate control of heating and stored hot water. Independent programs for heating and hot water.



General Information

Dimensions	140mm x 87mm x 37mm
Display	Backlit LCD
Clock	12 hour am/pm, 1 minute resolution, accuracy +/- 1.5 sec/day
Heating System	Pumped or Gravity

Power

Operating Voltage	100 ~ 240 VAC
Battery Type	Lithium Cell CR2032
IEC Protection Class	Class II

Construction

Material	Thermoplastics, Flame Retardant
Fixing	Surface Only
Wiring	Fixed wiring only

Outputs

Total Switch Rating	230V AC, 2(1)A (per channel)
Contact Type	1B , Micro-Disconnection

Programming

Programming Schedule	24 Hour, 5/2 Day and 7 Day Programmable
Available Operations	2 or 3 ON/OFF Periods
Modes Available	On, Off, Auto, All Day
Pre-Programmed Schedule	Yes
Summer/Winter Time Change	Yes; Automatic
Holiday Mode	Yes

Boosts

Selectable Durations	1,2 or 3 Hour Boost
-----------------------------	---------------------

Environment

Ingress Protection	IP30
Operating Temperature	0°C to 40°C

Features

- 24 hour, 5/2 day and 7 day selectable
- 2 or 3 ON/OFF periods selectable
- 1, 2 or 3 hour boost
- Advance to next programmed event
- Automatic Summer/Winter time change
- Standard wall plate - simple plug in and replace
- Pumped or gravity system selectable