

Technical Specification

Product Code: Q553.13.11

Description: Astro Zone 1, 4 Pin Time Switch, 1 On/Off & optional early off





General Information

Dimensions 146.5mm x 105.7mm x 82mm

Display 24 Hour Dial
Wire Gauge 0.5 - 4mm²
Time Base Quartz Crystal
Timing Accuracy 5 Minutes/Year

Power

Operating Voltage 230VAC
Power Consumption 0.6W @ 230V
Power Reserve 20 Days

IEC Protection Class Class I (Must be earthed)

Live Parts Protection Contained within the enclosure

Construction

Base Type 4 Pin

Fixing Surface Mounting

Outputs

Contact Type SPST
Total Switch Rating 20A, 230VAC

viewer Courset Bating (0.0nf 5.4

Maximum Current Rating (0.6pf 5A Inductive)

Maximum Current Rating (0.8pf 12A

Inductive)

Halogen, Filament Lamp 3600W Discharge (Sodium, Mercury, 3600W

Metal Halide)

Fluorescent Lamp 1980W LED 230VAC 3600W

Programming

Programming Schedule 24 Hour Program

Day Omission No

Temporary Override Facility Advance to "OFF", when program "ON"

(Manual Button) and will remain "OFF" unit next "ON"

operation and vice versa

Dial Calibration Zone 1
Setting Accuracy +/- 3 Minutes
Available Operations 1 ON/OFF Period
Sunrise/Sunset Time Offset (+/-) 45 Minutes

Early "Off" on selected day

Environment

Ingress Protection IP20
Operating Temperature 0°C to 50°C

Accessories

110469 FD930 Conduit Box Time Switch





