


SFX/OSP1-60-LSZH-GRY

OSP1-60 1pr 18AWG Overall Foil Screen 600V Grey LSZH (8760) CPR:Eca



Cable Construction	1 Pair
Conductor	Tinned Copper
Conductor Diameter (mm)	16 x 0.30
Stranded Diameter (mm)	0.81
Insulation	HDPE
Insulation Thickness (mm)	0.450
Insulation Diameter (mm)	2.05 ±0.10
Insulation Colour(s)	Black, Clear
Al-PET Shield	≥115%
Drain Wire	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	7 x 0.28
Jacket	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	5.50 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSP1-60 2x18AWG 600V Overall Screened LSF RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<25.00Ω/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation and panel wiring.