


SFX/OSC10-LSZH-GRY

OSC10 10 Core 24AWG Overall Foil Screen 600V Grey LSZH (9540) CPR:Eca



Cable Construction	10 Cores
Conductor	Tinned Copper
Conductor Diameter (mm)	0.19 ±0.008 x 7(0.22mm ²)
Stranded Diameter (mm)	0.22
Insulation	LSZH
Insulation Thickness (mm)	0.3
Insulation Diameter (mm)	1.20 ±0.10
Insulation Colour(s)	Red,Black,White,Green,Blue,Brown,Orange, Yellow, Violet, Grey
Al-PET Shield	>=115%
Drain Wire	
Drain Wire Conductor	Tinned Copper
Drain Wire Conductor Diameter (mm)	0.19 ±0.008 x 7
Jacket	LSZH
Jacket Thickness (mm)	0.70
Overall Diameter (mm)	6.20 ±0.20
Jacket Colour	Grey RAL 7042
Sheath Printing	OSC10 10x24AWG Overall Screened LSZH RoHS2 (PO) (m)
Reaction to Fire	Eca
Electrical Characteristics	
Max Conductor DC resistance @ 20°C	<90.00Ω/km
Rated Temperature (°C)	-40°C to 70°C
Rated Voltage (V)	600V
Insulation Resistance @20°C	>200MΩ/km
Standards	CE2014/30/EU, RoHS2 2011/65/EU, LVD 2014/35/EU
Application	Audio, control, instrumentation, panel wiring and RS232 applications.