

PROFESSIONAL LIGHTING

LED TAPE ACCESSORIES

PROFESSIONAL UNIVERSAL POWER SUPPLIES FOR LOW PROFILE LED TAPE



These IP66 rated power supplies are designed to be used by qualified people to install LED tape. Each has a different number of outputs and power to suit different requirements for each job.

- 2 or 4 outputs for loop output connection
- Professional use power supplies
- Waterproof IP66 rated



Power IN 170-250Vac, 50/60Hz
 Voltage out 12Vdc
 IP rating IP66

	153.744	153.745	153.747
Power OUT	60W	100W	150W
Output feeds	2	2	4
Current	5 amps	8.3 amps	12.5 amps
Dimensions	180 x 70 x 55mm	240 x 70 x 45mm	230 x 130 x 60mm
Weight	850g	1.2kg	2.75kg

Stock code	Power	Outer QTY	Packed
153.744	60W	10 Box	
153.745	100W	10 Box	
153.747	150W	5 Box	

RGB TAPE CONTROLLER WITH IR REMOTE



RGB controller for LED tape operated by an IR remote control for selecting the static colour, brightness or colour changing operating mode.

- Ideal for use in small applications
- 16 preset static colour modes
- 4 different colour changing modes of operation
- Adjustable brightness
- Supplied with small handheld IR remote
- IR remote controlled up to 10m (in line of sight)
- Mounting points for attachment to a wall or other surface



Power 12Vdc
 Power connection 2.1mm dc
 Max current per channel 3 x 2 amps
 Dimensions (remote) 85 x 55 x 8 mm
 Dimensions (controller) 35 x 50 x 25mm
 Weight (remote) 21g
 Weight (controller) 30g



Stock code	Outer QTY	Packed
153.741	50 Box	

RGB CONTROLLER WITH 17 PROGRAMS



This universal RGB LED tape controller has 17 built in programs which can be used to set the correct atmosphere for any type of use. Whether it be at home, in a car, at work or any professional type of installation this controller will have the program you need to get going.

- Suitable for medium to large installations
- 7 Preset static colour modes
- 10 present colour changing modes (colour switch, colour fade, strobe, RGB colour mixing and many more)
- 8 brightness levels
- 8 different speed modes for present colour changing modes
- Mounting points for attachment to a wall or other surface



Power 12/24Vdc
 Max current per channel 3 x 6 amps
 Dimensions 210 x 40 x 30mm
 Weight 137g



Stock code	Outer QTY	Packed
153.742	50 Box	