
Clean All Genius Spray

Revision: 8/12/2017

Page 1 from 1

Technical data

Basis	Solvent mixture
Consistency	Liquid
Density	Ca. 0,78 g/ml
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	97 %
Application temperature	5 °C → 30 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Clean All Genius Spray is a multifunctional, fast-drying cleaner for machine parts, floors and other various surfaces. Genius spray allows precise extrusion and regular spray action.

Properties

- Cleans and degreases
- Leaves no residue
- Fast drying
- Aerosol can be used in any angle (360°)
- Contains non flammable propellant

Applications

- Suitable for cleaning and degreasing mechanical parts. Also suitable for the preparation of surfaces
- for the application of sealants or adhesives. For the removal of uncured excess MS, PU or silicone
- sealants, tar residue, grease, wax,... Can be used on most surfaces (metal, plastics, PVC,...) and leaves no residue.

Packaging

Colour: transparent

Packaging: 300 ml aerosol

Parfum: Orange

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

All materials

Application method

Application method: Shake can well before use. Spray at a distance of appr. 20 cm of the object. Apply as required. After applying rub the surface dry with a clean towel. Always rub in one direction. Test for adverse effects on the surface in advance.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Remarks

- Due to the wide variety of possible plastics and paints and to avoid damage to the surface, a preliminary compatibility test is recommended.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.