
CONTACT SPRAY

Revision: 12/03/2009**Page 1 of 1****Technical data:**

Base	Mixture of mineral oils
Consistence	Liquid
Density	0,81 g/mL
Viscosity at 20°C	1 mPa.s
Flash point	52°C
Gel point	-62°C
Acidity pH	Neutral
Solubility	Completely soluble
VOC content	84%

Product:

Universal spray for the cleaning and maintenance of electric contact areas.

Applications:

- Suitable for electric contact points such as switches, stop contacts, batteries, measuring tools, etc
- Cleans and deoxidizes surfaces and improves the power transmission at electric contacts
- Prevents moisture penetration which could result in disturbances
- Also suitable for dehumidising of electric wirework and – tools.
- Ideal for electric installations, appliances, stop contacts and light switches....

Characteristics:

- Dissolves corrosion and oxidation
- Improves transmission
- Prevents loss of tension
- Reduces humidity
- Non corrosive
- Suitable for interior and exterior applications
- Aerosol can be used in any angle (360°)

Packaging:

Colour: transparent

Packaging: aerosol can of 400 ml / 6 units per box

Shelf Life:

3 years in unopened packaging in dry and cool surroundings at temperatures between +5°C and +25°C

Surfaces:

All types of metals and plastics

Instructions:

Shake can thoroughly before application. Ensure that all electric appliances are switched off before application. Wait 20 minutes before switching appliances on again.

Health and Safety Recommendations:

Use only in well-ventilated areas.

In case of contact with eyes, rinse immediately with plenty of water.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.