

Lubricate All Genius Spray

Revision: 8/12/2017

Page 1 from 1

Technical data

Basis	Mixture of white grease, PTFE and other solid lubricants
Consistency	Liquid
Density	Ca. 0,70 g/ml
Solubility in water	Not soluble
Volatile Organic Compounds (VOC)	76 %
Temperature resistance	-20 °C → 150 °C
Application temperature	5 °C → 30 °C

(*) these values may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Product description

Lubricate All Genius Spray is a high-grade lubricant based on a white grease and PTFE for the treatment of metal and plastic parts. Genius spray allows precise extrusion and regular spray action.

Properties

- Lubricates
- Reduces friction and wear
- Rust and corrosion-resistant
- Water-repellent
- Does not contain silicones
- For in and outdoor use
- Aerosol can be used in any angle (360°)
- Complies to NSF H1
- Contains non flammable propellant

Applications

- To be used for machines, roller bearings, axles, cogwheels, conveyer belts, rubber gasket profiles,...
- Suited for parts which are subject to long or high pressure and temperature loads (-20 to 150°C).
- Water resistant and protects against corrosion.
- Foodsafe, may be used in applications where incidental food contact may potentially occur

Packaging

Colour: White

Packaging: 300 ml aerosol

Shelf life

3 years in unopened packaging in a dry and cool environment at temperatures between +5°C and +25°C.

Substrates

Nature: clean, free of dust and grease.
All types of metals and plastics.

Application method

Application method: Surfaces must be cleaned, degreased and dry. Shake can well before use. Spray at a distance of appr. 20 cm of the object. To obtain the best result apply the spray while the moving parts are in motion if possible.

Health- and Safety Recommendations

Use only in well-ventilated areas. In case of contact with eyes, wash immediately with plenty of water.

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.