
MULTI SPRAY

Revision: 11/03/2009**Page 1 of 1****Technical data:**

Base	Mixture based on mineral oil
Consistency	Liquid
Specific Gravity	0,81 g/mL
Viscosity (20°C)	1 mPa.s
Flash point	52°C
pH Value	Neutral
Temperature resistance	-50°C till +190°C
Solubility in water	Fully soluble
VOC-content	84%

Product:

High-quality universal spray with 8-fold action:

1. rust dissolver
2. lubricant
3. cleaner
4. water-repellent
5. penetrating oil
6. corrosion-resistant
7. contact spray
8. shock spray

Applications:

To be used on screws, bolts, nuts, moving parts, axles, hinges, chains, garden tools, etc...

Is corrosion-resistant. Has a penetrating action and a protective film remains after cleaning Does not corrode plastics and metals. Prolongs the life of rubbers.

Characteristics:

- Lubricates
- Protects
- Rust and corrosion-resistant
- Water-repellant
- Removes dirt and grease
- Cooling and shrinking effect (shock spray)
- Silicone free
- For in and outdoor use
- Aerosol can be used in any angle (360°)

Packaging:*Colour:* white*Packaging:* aerosol of 400 ml**Shelf life:**

3 year in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C.

Surfaces:*Type:* all metals and synthetic materials.*State of surface:* clean, dry, free of dust and grease**Instructions:**

Clean the surface thoroughly, degrease and make it dry. Shake the canister before use.

Spray on approx. 20 – 25 cm distance from the surface. Apply as required. When used as contact spray, only switch electric installations back on when spray has evaporated. When used as a rust dissolver, wait for 5 to 10 min. To improve accuracy, change white nozzle by the black one.

Health and Safety Recommendation:

Apply only in a ventilated area.

In case of contact with eyes, wash with water and soap.

Remark: The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. In every case it is recommended to carry out preliminary experiments.