



ISC L-1625 Top

Order no. 018577

Equipment

- **Automatic impulse filter cleaning** - cleans the filters during suction operation - without air flow interruption for permanent operation!
- **New high-performance turbine** with better suction power
- Power socket with automatic ON/OFF
- Stepless speed controller
- Filter indicator light
- Soft start control & tracking electronics
- Water level detection with sensor shutdown
- Antistatic preparation
- Cable hook for cable storage
- Tube fixation by Velcro tape
- Accessories storage
- Robust, double-walled container suitable for construction sites
- Large, reinforced wheels and castors, flush, stable locks
- **New rotary slide:** Easy handling - facilitates the flexible use of fleece and PE bags.
- **New container** closure for dust-free transport
- Storage surface for tools and small parts

high dust emission



Technical Data

| | |
|---------------------------------------------------------|----------------------------|
| Power consumption max. | 1600 Watt |
| Air flow max. | 75 l/s* |
| Vacuum max. | 280 mbar* |
| Sound pressure level | 69 dB(A) |
| Container capacity (max.) I Gross-dust-water | 25 l; 20 l; 15 l; |
| Dimensions (L x W x H) (incl. push handle) | 45 cm x 39 cm x 49 cm |
| Weight | 12,2 kg |
| Power cord length | 8 m (rubber, H05RR-F), red |
| Operating range | 13,0 m – 14,0 m |

* Measured at the motor head

Scope of Supply

EWS accessory set consisting of:

- 1 x Suction hose (Ø 35 mm x 5 m)
- 1 x Stainless steel handle pipe with auxiliary air slide
- 2 x Stainless steel suction pipe (50 cm each)
- 1 x Crevice nozzle (22 cm)
- 1 x Connection sleeve (stepped)
- 1 x Dust nozzle 37 with hard floor insert
- 1 x Fleece filter bag FBV 25/35
- 1 x Velcro tape
- 2 x folded filter cassettes FKP 4800 M Adv. Polyester (dust class M, ≥ 99,9%)



IFA-certified vacuum cleaner for slightly hazardous dusts of dust class L, dust retention capacity 99 %.

**Dust-free and therefore healthier working!
More safety in the workplace!**