



iPulse M-1635 Safe Plus

Order no. 018638



· Automatic impulse filter cleaning - cleans the filters during suction operation - without air flow interruption for permanent operation!

- Demand-driven by pressure differential measurement!
- Cleaning of the filter cassettes with forces corresponding to 300 times the acceleration due to gravity (300 g) perfectly suited for fine and problematic dusts (e.g.
- New high-performance turbine with better suction power
- Smartfix fixation of Systainer tool boxes. Innovative railings offer additional possibilities, e.g. the fixing of the suction hose with Velcro straps.
- Push handle for comfortable driving of the vacuum cleaner
- · Power socket with automatic ON/OFF
- · 2-stage speed regulation
- Air flow monitoring with acoustic warning signal / preselection switch for different hoseØ
- · Filter indicator light
- · Soft start control & tracking electronics
- · Water level detection with sensor shutdown
- · Antistatic preparation
- · Carrying handle with fold-out cable hook
- Accessories optimally accommodated: 4 parking positions at the rear and 2 holders on the upper part
- Robust, double-walled container suitable for construction sites
- Large, reinforced wheels and castors, flush, stable locks
- New rotary slide: Easy handling facilitates the flexible use of fleece and PE bags.
- New container closure for dust-free transport

IFA-certified vacuum cleaner for slightly hazardous dusts of dust class M, dust retention capacity 99 %.

> Dust-free and therefore healthier working! More safety in the workplace!

Technical Data

1600 Watt
75 l/s*
280 mbar*
69 dB(A)
35 l; 25 l; 22 l;
66 cm x 40 cm x 92 cm
16,8 kg
8 m (Gummi, H07RN-F), rot
13,0 m

^{*} Measured at the motor head

Scope of Supply

- 1 x Antistatic suction hose (Ø 35 mm x 5 m)
- 1 x Connection sleeve (stepped)



2 x Velcro tape

- 2 x folded filter cassettes FKP 4800 M Adv. Polyester (dust class M, ≥ 99,9%)
- 3 x Special PE disposal bags









