LED floodlight without sensor

XLED ONE XL

Anthracite EAN 4007841 065225 Article number 065225







3000 K

















long life LEI 50.000 h

warm-white

IP44 Panel 180° vertical

ndoor/outd light

energy saving

manufacture's warranty steinel.de/garantie3y

CE

ight source not exchangeable

Control gear n exchangeable

Function description

Powerful lighting very big on style. The XLED ONE XL with an output of 42,6 W delivers a powerful 3000 K and 4200 lm of warm white light. Tilting through 180°, the wall and ceiling spot is fitted with high-quality and particularly long-lasting LEDs with a service life of a good 30 years – without any ifs or buts. Protection class: IP44

Technical specifications

193 x 259 x 215 mm
Yes, STEINEL LED system
No
3 years
Anthracite
4007841065225
Outdoors
outdoors, courtyard & driveway
wall, ceiling
Wall, Ceiling, Surface wiring
IK03
IP44
I
-20 - 40 °C
Aluminium

Mains power supply	220 – 240 V / 50 – 60 Hz
Output	25 - 50 W
Photo-cell controller	No
Luminous flux total product	4200 lm
Measured luminos flux (360°)	4200 lm
Total product efficiency	99 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index	80-89
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 36000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Basic light level function	No

LED floodlight without sensor

XLED ONE XL

Anthracite EAN 4007841 065225 Article number 065225



Dimension Drawing

