

Photo-cell controller

NightMatic 3000 Vario

white

EAN 4007841 550615



Twilight switch +
eco-mode

1000w

1000 W max.



IP54



0.5 - 10 lux



energy saving



3 JAHRE
HERSTELLER
GARANTIE
steinel.de/garantie



CE



TÜV Nord
Baumuster
checked

Function description

Intelligent lighting control. Photo-electric lighting controller NightMatic 3000 VARIO, for controlling lighting systems for building fronts, properties, shop windows etc., automatically switches light 'ON' at dusk automatically 'OFF' again at dawn, with selectable night economy mode.

Technical specifications

Dimensions (L x W x H)	37 x 74 x 99 mm
Mains power supply	230 – 240 V / 50 Hz
Power consumption	0,8 W
Sensor Technology	Light sensor
Application, place	Outdoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall
Installation	Surface wiring
Twilight setting	0,5 – 10 lx
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / 4 pcs. fluorescent lamps	

Basic light level function	No
Functions	Night economy mode, light ON / OFF in the morning
Settings via	Potentiometers
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white
PU1, EAN	4007841550615

Photo-cell controller

NightMatic 3000 Vario

white

EAN 4007841 550615



Dimension Drawing

