LED floodlight without sensor

XLED ONE XL

Anthracite EAN 4007841 065225 Article number 065225







3000 K









3 years









long life LED 50.000 h

3000K warm-white

IP44

Panel 180° vertical

indoor li

outdoor ht energy sa

warranty steinel.de/ garantie3y

Subject to technical modifications

Light source not exchangeable

Control gear not exchangeable



Function description

Powerful lighting very big on style. The XLED ONE XL with an output of 42,6 W delivers a powerful 3000 K and of warm white light. Tilting through 180°, the wall and ceiling spot is fitted with high-quality and particularly long-lasting LEDs with a service life of a good 30 years – without any ifs or buts. Protection class: IP44.

Technical specifications

Dimensions (L x W x H)	193 x 259 x 215 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	3 years
Version	Anthracite
PU1, EAN	4007841065225
Application, place	Outdoors
Application, room	outdoors, courtyard & driveway
Installation site	wall, ceiling
Installation	Wall, Ceiling, Surface wiring
Impact resistance	IK03
IP-rating	IP44
Protection class	ı
Ambient temperature	-20 - 40 °C
Housing material	Aluminium

Cover material	Glass transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Photo-cell controller	No
Luminous flux total product	4200 lm
Total product efficiency	99 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 36000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Basic light level function	No
Output	42,6 W
Colour Rendering Index CRI	= 80


LED floodlight without sensor

XLED ONE XL

Anthracite EAN 4007841 065225 Article number 065225



Dimension Drawing



Circuit diagram

