


Outdoor light

L 910 LED

EAN 4007841576202



Functional description

Same technology, even more effective: if you are looking for somewhat more ambient light on the outside of your home, we can offer you an uplight/downlight solution with the L 910 LED that's just as stylish as it is efficient. As with its little brother, no-maintenance and low-consumption LEDs give you aesthetically pleasing ambient lighting here too whenever you wish thanks to the reliable IR sensor. And if you interconnect them, they will also switch on and off simultaneously. An effect not only appreciated by admirers of aesthetic style.

Technical specifications

Dimensions(w x h x d):	235 x 80 x 85 mm
Voltage	220-240 V, 50/60 Hz
Sensor type	Passive infrared
Output	11 W
Luminous flux	755 lm
Efficiency	68.6 lm/W
Light colour	3000 K / SDCM 3
Colour rendering	Ra ≥ 80
LED life expectancy	50,000 h
LED cooling system	Passive Thermo Control
Detection angle	180°
Reach	5m or 12 m, selectable
Time setting	2 min. or 15 min.
Basic light level	Effect lighting on the wall
Response brightness	2 - 20 lx
Soft light start	Yes
Manual override	selectable, 4h
Degree of protection (IP)	IP44
Protection class	II
Impact strength	IK00
Temperature range	-20°C to +50°C
Material	Aluminium, UV-resistant plastic
With lamp	STEINEL LED system
Lamp replaceable	No
Version	Anthracite