

Motion detector

sensIQ S

EAN 4007841034979

**Functional description**

Handsome addition! The sensIQ S is just as perfect in form and functional diversity as its larger role model. A look that architects like. This designer motion detector was developed specifically for wall mounting though. Being altogether more compact than its big brother, the sensIQ S nestles up against the facade, perfectly harmonising with modern, purist architecture. Its inner values are spectacular too because it comes with the same highly intelligent features and setting options as the sensIQ.

Technical specifications

Model	Movement sensor
Sensor type	Passive infrared
Accessories	includes corner wall mount and remote control RC9
Detection angle	300° with 180° angle of aperture
Reach	Adjustable in 3 directions via control dial, (2 – 20 m max. tangential, temperature-stabilised)
Reach	(2 - 20 m max. tangential, temperature-stabilised) adjustable in 3 directions via control dial
Application	indoors and outdoors
Installation	Wall Corner
Recommended installation height	2-5 m
Dimensions(w x h x d):	114 x 74 x 128 mm
Voltage	100 - 240 V, 50/60 Hz (2.5 mm ² max.)
max. output (resistive load, all-purpose lamp)	1200 W max. at 120 V 2000 W max. at 230 V
max. output (uncorrected, inductive, cos φ = 0.5, e.g. fluorescent lamps)	1000 VA max., 230 V 500 VA max., 120 V
Capability of masking out individual segments	Yes
Sensor system	4 sensors, 6 levels for long-distance detection and 5 for sneak-by guard, 1360 switching zones
Teach-function for response value luminosity	Yes
Time setting	5 sec. - 15 min. Pulse mode (approx. 2 sec.)
Manual override	selectable, 4h
Permanently 'OFF'	selectable
Response value luminosity	2-2000 lx
Degree of protection (IP)	IP54
Temperature	-20-50 °C
Version	Black

Data sheet



Motion detector

sensIQ S

EAN 4007841034979

Sensorenerfassungsbereich 1

Image not found or type unknown

