


Floodlight

XLED home 2 XL

EAN 4007841030049



Functional description

The powerful XLED home 2 XL sensor-switched outdoor floodlight is the first choice for those who like it particularly bright or need to illuminate large areas. Innovative, highly efficient LEDs ensure the perfect illumination of driveways, courtyards and gardens. With an energy consumption of just 20 watts. The XLED home 2 XL is also a moving wonder. The fully swivelling LED panel ensures maximum flexibility. In combination with the opal cover, the floodlight ensures optimum lighting conditions around the home with a colour temperature of 4000 K. The XLED home 2 XL is available as an individual floodlight or as a slave version. Available in white, black, graphite and silver.

Technical specifications

Luminous flux	1608 lm
Output	20 W
Light colour	4000 K / SDCM 3
Detection angle	140° with sneak-by protection
Reach	14 m
Floodlight positioning range	180° horizontally, 180° vertically
Sensor swivelling range	180 °
Sensor tilting range	90 °
Sensor type	Passive infrared
Dimensions(w x h x d):	214 x 180 x 161 mm
Voltage	230 - 240 V, 50 Hz/60 Hz
Mains power	97 mA
Power factor	0.86
Max. Output	Max. 1000 W, max. 4 fluorescent lamps / LED lamps, C < 88 µF
Efficiency	80 lm/W
Colour rendering	Ra ≥ 80
LED cooling system	HCMC (High Conductive Magnesium Composite)
LED life expectancy	50,000 h (L70B10 to LM80)
Time setting	8 sec. - 35 min.
Degree of protection (IP)	IP44
Protection class	II
Material	UV-resistant plastic
Temperature range	-20°C - +40°C
With lamp	STEINEL LED system
Lamp replaceable	No
Version	Black