


## Floodlight

**XLED curved**

EAN 4007841012076

**Functional description**

The compact outdoor floodlight XLED curved is ideal for illuminating building entrances and pathways. Yet the practical floodlight doesn't only satisfy safety and security needs, in conjunction with the house facade it also unfurls a pleasantly charming lighting effect. Both the sensor and the entire outdoor floodlight come in a pleasingly understated, unobtrusive look, clearly leaving centre stage to the lighting in setting off buildings and outdoor areas with masterful proficiency.

**Technical specifications**

<b>Luminous flux</b>	830 lm
<b>Output</b>	10,5 W
<b>Light colour</b>	4000 K / SDCM 4
<b>Detection angle</b>	160° with sneak-by guard
<b>Reach</b>	8 m max.
<b>Sensor swivelling range</b>	30 °
<b>Sensor type</b>	Passive infrared
<b>Dimensions(w x h x d):</b>	120 x 160 x 107 mm
<b>Voltage</b>	230 - 240 V, 50 Hz/60 Hz
<b>Efficiency</b>	79 lm/W
<b>Colour rendering</b>	Ra ≥ 80
<b>LED cooling system</b>	Active and Passive Thermo Control
<b>LED life expectancy</b>	50,000 h (L70B10 to LM80)
<b>Time setting</b>	2 sec. - 70 min.
<b>Degree of protection (IP)</b>	IP44
<b>Protection class</b>	I
<b>Material</b>	UV-resistant plastic with aluminium heat sink
<b>Temperature range</b>	-20°C - +40°C
<b>With lamp</b>	STEINEL LED system
<b>Lamp</b>	LED system
<b>Lamp replaceable</b>	No
<b>Version</b>	Anthracite
<b>Weight</b>	0.57 kg