


Floodlight

XLED slim

EAN 4007841012069

**Functional description**

When visitors arrive, light comes into play with the economical outdoor floodlight XLED slim. This stylish lighting solution captivates with its elegant design and provides attractive illumination for building entrances and pathways. On building facades the XLED slim makes attractive lighting statements that not only look good but also ensure you get home safely. At the same time, the unobtrusive floodlight with its almost invisible sensor blends into the background with visual discretion.

Technical specifications

Luminous flux	660 lm
Output	10,5 W
Light colour	4000 K / SDCM 4
Detection angle	160° with sneak-by guard
Reach	8 m max.
Sensor swivelling range	30 °
Sensor type	Passive infrared
Dimensions(w x h x d):	241 x 66 x 201 mm
Voltage	230 - 240 V, 50 Hz/60 Hz
Efficiency	62.9 lm/W
Colour rendering	Ra ≥ 80
LED cooling system	Active and Passive Thermo Control
LED life expectancy	50,000 h (L70B10 to LM80)
Time setting	2 sec. - 70 min.
Degree of protection (IP)	IP44
Protection class	I
Material	UV-resistant plastic with aluminium heat sink
Temperature range	-20°C - +40°C
With lamp	STEINEL LED system
Lamp replaceable	No
Version	White