**Motion detector - Professional Line** 

IS 300 black EAN 4007841 602116







#### **Function description**

One for every corner. Infrared motion detector IS 300, for indoors and out, ideal for corner situations, irregular shaped spaces, corridors, installation height 2 m, 300° angle of coverage, max. reach 12 m (tangential), selectable time and twilight threshold, turning sensor head (80°) for precision targeting.

# **Technical specifications**

Туре	Motion detectors
Dimensions (L x W x H)	95 x 60 x 85 mm
Mains power supply	230 – 240 V / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Surface wiring
Switching zones	456 switching zones
Electronic scalability	No
Mechanical scalability	No
Mounting height	1,80 – 4,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 3 m (24 m <sup>2</sup> )

Reach, tangential	r = 12 m (377 m <sup>2</sup> )
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	10 s – 15 Min.
Switching output 1, resistive	2000 W
Constant-lighting control	No
Basic light level function	No
Settings via	Potentiometers
With remote control	No
Interconnection	No
IP-rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	black
Colour, RAL	9005
Manufacturer's Warranty	5 years
Version	black
PU1, EAN	4007841602116

IS 300 black EAN 4007841 602116




### Accessories

EAN 4007841 630119	Corner wall mount 01
EAN 4007841 630218	Corner wall mount 01

# **Detection Zone**

# **Dimension Drawing**



Mögliche Montagehöhe: 1,80 m – 4,00 m Orange: radial Schwarz: tangential

