


LED Floodlight

Spot ONE

Slave

EAN 4007841 058623



LED

20.000 h



3000K
warm-white



38°



IP44



180° horizontal,
90° vertical



3 JAHRE
HERSTELLER
GARANTIE
steinel.de/garantie



CE

Function description

Spot on! The purist swivelling LED wall spot ONE in aluminium comes with timeless aesthetic appeal for selective lighting all around the building. Can be interconnected with the "Spot ONE Sensor" master version by cable or simply used on its own as a powerfully bright individual solution. 520 lm light output from only 7 W. Includes lamp (GU-10-LED).

Technical specifications

Dimensions (L x W x H)	175 x 97 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	7 W
Luminous flux	520 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index CRI	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	No
Photo-cell controller	No
Basic light level function	No

Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	0,562 kg
Version	Slave
PU1, EAN	4007841058623

LED Floodlight

Spot ONE

Slave

EAN 4007841 058623



Dimension Drawing

