


# Spot DUO

Sensor

EAN 4007841 058647



**LED**

20.000 h



3000K  
warm-white



38°



2x Infrared sensor  
90°



max. 10 m



IP44



180° horizontal,  
90° vertical



2 - 1000 lux



8 sec - 35 min



networkable via  
cable

## Function description

Powerfully bright LED duo. Wall spot DUO Sensor with two swivelling spotlight heads (180° horizontally, 90° vertically), each with 90° infrared sensor (10 m reach). 2 x 520 lm from 2 x 7 W for optimum illumination all around the building. With time setting (8 s - 35 min) and twilight setting (2-1000 lux). Several spots can be interconnected by cable. Includes 2 GU-10 LED lamps.

## Technical specifications

Dimensions (L x W x H)	175 x 247 x 98 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Mounting height max.	2,50 m
Sensor Technology	passive infrared
Output	15 W
Interconnection	Yes
Luminous flux	1040 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index CRI	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Sneak-by guard	No
Capability of masking out individual segments	No
Reach, radial	passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m <sup>2</sup> )

Reach, tangential	passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m <sup>2</sup> )
Photo-cell controller	Yes
Twilight setting	2 – 1000 lx
Time setting	8 s – 35 Min.
Basic light level function	No
Soft light start	No
Continuous light	selectable
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
PU1, net weight	1,12 kg
Version	Sensor
PU1, EAN	4007841058647

Sensor-switched LED floodlight


# Spot DUO

Sensor

EAN 4007841 058647



## Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

## Dimension Drawing

