


Spot Way

Sensor Connect

EAN 4007841 058661



LED

20.000 h



3000K
warm-white



38°



Infrared sensor
90°



max. 10 m



Twilight switch



IP44



180° horizontal,
90° vertical



2 - 1000 lux



5 sec - 60 min

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 520 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

| | | | |
|---|---|----------------------------|---|
| Dimensions (L x W x H) | 226 x 140 x 572 mm | Reach, tangential | passive infrared: Passiv Infrarot: r = 10 m (Passiv Infrarot: 79 m ²) |
| Mains power supply | 220 – 240 V / 50 – 60 Hz | Photo-cell controller | Yes |
| Mounting height max. | 2,50 m | Twilight setting | 2 – 2000 lx |
| Sensor Technology | passive infrared | Time setting | 5 s – 60 Min. |
| Output | 7 W | Basic light level function | No |
| Interconnection | Yes | Functions | Digital timer, Master/slave override |
| Slave mode/selectable | Yes | Soft light start | No |
| Luminous flux | 520 lm | Continuous light | selectable, 4h |
| Colour temperature | 3000 K | Impact resistance | IK03 |
| Colour variation LED | SDCM5 | IP-rating | IP44 |
| Colour Rendering Index CRI | 80-89 | Protection class | II |
| With lamp | Yes, LED lamp | Ambient temperature | -20 – 40 °C |
| Lamp | LED can be replaced | Housing material | Aluminium |
| With motion detector | Yes | Cover material | Plastic, transparent |
| Detection angle | 90 ° | Manufacturer's Warranty | 3 years |
| Angle of aperture | 90 ° | PU1, net weight | 1,23 kg |
| Sneak-by guard | No | Version | Sensor Connect |
| Capability of masking out individual segments | No | PU1, EAN | 4007841058661 |
| Reach, radial | passive infrared: Passiv Infrarot: r = 2 m (Passiv Infrarot: 3 m ²) | | |

Sensor-switched LED floodlight


Spot Way

Sensor Connect

EAN 4007841 058661



Detection Zone



Mögliche Montagehöhe: 1,80 m – 2,50 m

Orange: radial

Schwarz: tangential

Dimension Drawing

